

Datasheet

Hydraulic Power Unit (HPU)



Performance Data:

Max Oil Pressure:	250 bar
Max Oil Flow:	160 L/min
Hydraulic Oil Tank Capacity	400L
Main Power Supply:	400/690 – 50/60hz
Power:	60 kW
Operating Temperature	-7 to +40 °C
ATEX	II 3G Ex db be IIB T3 Gb

Connections:

Pressure out	Snap-tite 3/4" Female
Return:	Snap-tite 3/4" Male
Drain:	Snap-tite 3/8" Male
Load Sense:	Snap-tite 3/8" Female
Oil Tank filling line:	Snap-tite 3/4" Female
Oil tank Drain line:	Snap-tite 3/4" Male
Power cable:	H07RNF 4G35MM ²

Weight & Dimensions:

Max. Gross Weight:	3000 Kg
Outer Dimensions (L x W x H):	2000mm x 1200mm x 1905mm
Lifting Devices:	4 points lifting chains

Classification: ATEX 2014/34/EU, Machinery Directive 2006/42/EC DNV GL 2.7-1, NORSOK Z-015

Fluid Control AS - Sola/Stavanger

Ljosheimsvegen 1
4050 SOLA, Norway

tel: +47 51 64 49 50
post@fluidcontrol.no



www.fluidcontrol.no

Copyright © 2013 Fluid Control. All rights reserved